



Our Docket No: 004906.P003

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

Suhail Nanji

Application No: 09/699,198

Filed: October 27, 2000

For: TUNNELING ETHERNET

Examiner: Phirin Sam

Art Unit: 2661

Confirmation No.: 6605

DECLARATION OF SUHAIL NANJI
Pursuant to 37 C.F.R. § 1.132

Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

I, Suhail Nanji hereby declare that:

1. Redback Networks Incorporated is the assignee of the above-identified patent application.
2. I have reviewed the above-identified patent application, including the claims. I am the inventor of the invention claimed in the above-identified patent application.
3. As a Redback Networks Incorporated employee, I was assigned the responsibility of developing Ethernet over Layer 2 Tunneling Protocol techniques for the Redback Networks Access Operating System, Release 3.1, an operating system manufactured by Redback Networks Incorporated.
4. The invention claimed in the above-identified patent application was embodied in the Redback Networks Access Operating System, Release 3.1.
5. I have reviewed the Redback Networks publications cited by the Patent Examiner in the application. The Redback Networks publications are entitled "Access Operating System Configuration Guide 3.1", dated 1999; "Access Operating System Command Reference Guide 3.1", dated 2000; and "Release Note for Redback AOS, Release 3.1.4", dated April 2000." A copy of the Redback Networks publications are attached hereto as Exhibits A, B,

Serial No. 09/699,198
Attorney Docket 004906.P003

and C, respectively. These publications are manuals for the Redback Networks Access Operating System, Release 3.1.

6. The subject matter related to my invention disclosed in the Redback Networks publications is attributable to me and was published on my behalf.

I, Suhail Nanji, hereby declare that all statements herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made knowing that willful false statements and the like are punishable by fine or imprisonment, or both under § 1001 of Title 18 of United States Code, and such willful or false statements may jeopardize the validity of the above-identified application or any patent issuing therefrom.

Respectfully submitted,

Date: 5/4/2005

Suhail Nanji
Suhail Nanji

FIRST CLASS CERTIFICATE OF MAILING
(37 C.F.R. § 1.8(a))

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail with sufficient postage in an envelope addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231

on

5/5/05
Date of Deposit

Cher, Clinkbeard
Name of Person Mailing Correspondence

Clinkbeard
Signature

5/5/05
Date

Ex. A

Access Operating System (AOS) Configuration Guide

**Release 3.1
Part Number 220-0122-01**



Corporate Headquarters
Redback Networks, Inc.
1389 Moffett Park Drive
Sunnyvale, CA 94089-1134
USA
<http://www.redback.com>
Tel: 408-548-3500

Rights and Restrictions

All statements, specifications, recommendations, and technical information contained are current or planned as of the date of publication of this document. They are reliable as of the time of this writing and are presented without warranty of any kind, expressed or implied. In an effort to continuously improve the product and add features, Redback Networks, Inc. ("Redback") reserves the right to change any specifications contained in this document without prior notice of any kind.

Redback shall not be liable for technical or editorial errors or omissions which may occur in this document. Redback shall not be liable for any indirect, special, incidental or consequential damages resulting from the furnishing, performance, or use of this document.

The following information is for FCC compliance of Class A devices: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio-frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case users will be required to correct the interference at their own expense.

Any modifications to this product not authorized by Redback could void the FCC approval and negate the user's authority to operate the product.

Limited Hardware Warranty and Disclaimer

Limited Warranty. Redback warrants to the original purchaser of the product ("Purchaser") only that the hardware sold hereunder shall be free of defects in material and workmanship and shall perform, under normal use and circumstances, in accordance with Redback's published specifications for a period of ninety (90) days from the shipment date. In the event that Redback receives notice from Purchaser during the warranty period that any hardware does not conform to its warranty, Redback shall, at its sole option (and as Purchaser's sole remedy), either repair or replace the non-conforming hardware, or refund the purchase price of such unit. Hardware replaced under the terms of any such warranty may be refurbished or new equipment substituted at Redback's option. This warranty is the only warranty made by Redback with respect to the hardware delivered hereunder and may be modified, amended or supplemented only by a written instrument signed by a duly authorized officer of Redback and accepted by Purchaser.

Procedures. A hardware item may only be returned with the prior written approval of Redback. Any such approval shall reference a return material authorization number issued by authorized Redback service personnel. Transportation costs, if any, incurred in connection with the return of a defective item to Redback shall be borne by Purchaser. Any transportation costs incurred in connection with the re-delivery of a repaired or replaced item to Purchaser shall be borne by Redback; provided that, such costs shall be borne by Purchaser if Redback reasonably determines that the item is not defective. If Redback determines, in its sole discretion, that the allegedly defective item is not covered by the terms of the warranty provided hereunder or that a warranty claim is made after the warranty period, the cost of repair by Redback, including all shipping expenses, shall be reimbursed by Purchaser.

Exclusions. The foregoing warranties and remedies are for Purchaser's exclusive benefit and are non-transferable. The foregoing warranties do not apply to any hardware which (1) has been altered, except as authorized by Redback, (2) has not been installed, operated, repaired, or maintained in accordance with any installation, handling, maintenance, or operating instructions supplied by Redback, (3) has been subjected to unusual physical or electrical stress, misuse, negligence, or accident (4) is used in ultrahazardous activities, (5) has been damaged or rendered unserviceable by installation or use outside of environmental specifications, or (6) has been exported from the original country of destination. In no event does Redback warrant that Purchaser will be able to operate its networks without problems or interruptions.

Third Party Products. Where a product not manufactured by Redback is sold by Redback hereunder to complete an order, the warranty coverage on that product is limited to its original manufacturer's warranty to the Purchaser, if any.

THE LIMITED WARRANTIES SET FORTH ABOVE ARE IN LIEU OF ALL OTHER WARRANTIES, WHETHER EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE, AND REDBACK SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. REDBACK DOES NOT WARRANT THAT THE PRODUCTS WILL MEET PURCHASER'S REQUIREMENTS OR THAT THE OPERATION OF THE PRODUCTS WILL BE UNINTERRUPTED OR ERROR FREE.

Software License Agreement

CAREFULLY READ THE FOLLOWING TERMS AND CONDITIONS. BY INSTALLING AND USING SOFTWARE INCLUDED WITH THE REDBACK PRODUCTS, YOU ARE AGREEING TO BE BOUND BY THESE TERMS AND CONDITIONS. IF YOU DO NOT AGREE TO THESE TERMS AND CONDITIONS, DO NOT USE THE REDBACK PRODUCTS.

1. SOFTWARE

The software covered by this license agreement includes (i) all Redback proprietary software provided with the product, whether provided on magnetic media or embedded in the product as firmware, and (ii) any third party owned software licensed to Redback and provided by Redback with the product (jointly, the "Software"). The following third party Software may be included with your product and is subject to this software license agreement:

- a. SNMP Monolithic Agent. Copyright © 1992-1998 SNMP Research International, Inc. All rights reserved.
 - b. VxWorks. Copyright © 1984-1998 Wind River Systems, Inc. All rights reserved.
 - c. The Redback Networks adaptation and implementation of the UDP and TCP protocols developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. Copyright © 1982, 1986, 1988, 1990, 1993, 1995 The Regents of the University of California. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: (1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. (2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. (3) All advertising materials mentioning features or use of this software must display the following acknowledgment: This product includes software developed by the University of California, Berkeley and its contributors. (4) Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
 - d. Point-to-Point Protocol (PPP). Copyright © 1989, Carnegie-Mellon University. All rights reserved. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.
-

e. Dynamic Host Configuration Protocol (DHCP) developed by The Internet Software Consortium. Copyright © 1997, 1998. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: (1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. (2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. (3) Neither the name of The Internet Software Consortium nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

2. LICENSE

Redback hereby grants to the original end user of the products ("Licensee") only, and Licensee hereby accepts, a personal, non-transferable, non-exclusive license to use the Software and related product documentation (the "Documentation") in accordance with the terms and conditions of this agreement.

Licensee may use the Software solely with the original Redback products or system with which it is provided (the "System"). Licensee may not transfer the Software to or use the Software on any equipment other than the System, whether or not such other equipment shall have been manufactured by Redback. This license shall expire upon sale of the System by Licensee.

Licensee agrees not to make any copies of the Software or the Documentation, in whole or in part, other than one permitted copy of the Software and Documentation which Licensee may maintain for archival purposes only. Licensee agrees not to modify, translate, reverse engineer, de-compile, disassemble, or create derivative works based on the Software, except to the extent that the foregoing may not be prohibited by applicable law.

Licensee agrees to take reasonable steps to safeguard copies of the Software against disclosure, copying or use by unauthorized persons, and to take reasonable steps to ensure that the provisions of this license are not violated by Licensee's employees or agents.

3. TITLE

Licensee acknowledges and agrees that all right, title and interest in and to the Software and Documentation, including all intellectual property rights therein, shall remain the property of Redback or its suppliers, subject only to the limited license to use granted to Licensee hereunder. This license is not a sale and does not transfer to Licensee any title or ownership in or to the Software or the Documentation or any patent, copyright, trade secret, trade name, trademark or other proprietary or intellectual property rights related thereto.

4. NONTRANSFERABILITY

Licensee may not rent, transfer, assign, sublicense or grant any rights in the Software or Documentation, in full or in part, to any other person or entity.

5. NO SOFTWARE WARRANTY

Redback warrants to Licensee only that the media on which the Software is recorded shall be free from defects in materials and workmanship under normal use for a period of ninety (90) days from the date of shipment by Redback. Licensee's sole and exclusive remedy, and Redback's sole and exclusive liability, shall be replacement of the media in accordance with this limited warranty.

THE SOFTWARE IS PROVIDED "AS IS." REDBACK EXPRESSLY DISCLAIMS AND NEGATES ALL WARRANTIES FOR THE SOFTWARE, WHETHER EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE, AND REDBACK SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF INTELLECTUAL PROPERTY OR OTHER VIOLATION OF RIGHTS. REDBACK DOES NOT WARRANT THAT THE SOFTWARE WILL MEET PURCHASER'S REQUIREMENTS OR THAT THE OPERATION OF THE SOFTWARE WILL BE UNINTERRUPTED OR ERROR FREE.

Some states or countries do not allow exclusion or limitation of incidental or consequential damages or limitation on how long an implied warranty lasts, so the above limitations or exclusions may not apply to Licensee. This warranty gives Licensee specific legal rights and Licensee may also have other rights, which vary from state to state or country to country.

6. TERMINATION

This agreement shall continue in effect until terminated hereunder. This agreement shall terminate automatically on Licensee's failure to comply with any of the restrictions and provisions herein, including without limitation any attempt to transfer this license. Upon any termination of this agreement, Licensee agrees promptly to destroy or return to Redback all copies of the Software and Documentation, including without limitation all original and archival copies thereof. No refunds shall be given for such returned materials. Notwithstanding any termination of this License, the rights and obligations set forth in Sections 3 (Title), 4 (Non-transferability), 5 (Limited Software Warranty), 6 (Termination), 7 (Limitation of Liability) and 8 (Miscellaneous) shall survive such termination.

7. U.S. GOVERNMENT RESTRICTED RIGHTS

The Software and Documentation are provided with Restricted Rights. Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 or subparagraphs (c) (1) and (2) of the Commercial Computer Software—Restricted Rights at 48 CFR 52.227-19, as applicable. Manufacturer is Redback Networks, Inc., 1389 Moffett Park Drive, Sunnyvale, California 94089.

8. MISCELLANEOUS

a. Licensee may not assign or transfer any of its rights or delegate any of its obligations under this agreement. Any attempted assignment or delegation by Licensee shall be null and void.

b. No delay, failure or waiver by either party to exercise any right or remedy under this agreement shall operate to limit, preclude, cancel or waive any exercise of such right or remedy or the exercise of any other right or remedy.

c. This agreement shall be governed by and construed in accordance with the laws of the State of California without regard to conflict of laws principles and without regard to the 1980 U.N. Convention on Contracts for the International Sale of Goods. The federal and state courts of California shall have exclusive jurisdiction and venue to adjudicate any dispute arising out of this agreement, and Licensee expressly consents to (i) the personal jurisdiction of the state and federal courts of California and (ii) service of process being effected upon it by registered mail sent to the Licensee.

d. If any provision in this agreement shall be found or be held to be invalid or unenforceable in any jurisdiction in which this agreement is being performed, then the meaning of said provision shall be construed, to the extent feasible, so as to render the provision enforceable, and if no feasible interpretation would save such provision, it shall be severed from the remainder of this agreement, which shall remain in full force and effect. In such event, the parties shall negotiate, in good faith, a substitute, valid and enforceable provision, which most nearly effects the parties' intent in entering into this agreement.

e. This software license agreement incorporates the General Limitation of Liability and Damages provisions set forth below.

f. This agreement constitutes the entire agreement between Licensee and Redback with respect to the subject matter of this agreement and shall supersede all prior oral or written understandings, communications or advertising. This agreement may be amended or modified only in writing signed by both parties.

Limitation of Liability and Damages

THE FOLLOWING LIMITATION OF LIABILITY AND DAMAGES APPLIES TO ALL HARDWARE, SOFTWARE AND DOCUMENTATION SOLD, LICENSED OR OTHERWISE DISTRIBUTED BY REDBACK OR ITS RESELLERS.

IN NO EVENT SHALL REDBACK, ITS SUPPLIERS OR ITS DISTRIBUTORS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGE, INCLUDING WITHOUT LIMITATION LOSS OF DATA, LOST PROFITS OR COST OF COVER, ARISING FROM THE USE OF THE HARDWARE, SOFTWARE OR DOCUMENTATION OR ANY DEFECT IN THE HARDWARE, SOFTWARE OR DOCUMENTATION, HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY. THIS LIMITATION SHALL APPLY EVEN IF REDBACK, ITS SUPPLIERS OR ITS DISTRIBUTOR SHALL HAVE BEEN ADVISED OF THE POSSIBILITY OF ANY SUCH DAMAGE. IN PARTICULAR, BUT WITHOUT LIMITATION, REDBACK, ITS SUPPLIERS AND ITS DISTRIBUTORS SHALL HAVE NO LIABILITY FOR THE LOSS OF ANY INFORMATION STORED OR COMMUNICATED OR ATTEMPTED TO BE STORED OR COMMUNICATED WITHIN ANY REDBACK SYSTEM USING THE HARDWARE OR SOFTWARE.

THE MAXIMUM AGGREGATE LIABILITY OF REDBACK AND ITS SUPPLIERS FOR ANY CLAIM ARISING OUT OF USE OF THE HARDWARE, SOFTWARE OR DOCUMENTATION OR ANY DEFECT IN THE HARDWARE, SOFTWARE OR DOCUMENTATION, ON ANY AND ALL THEORIES OF LIABILITY, INCLUDING WITHOUT LIMITATION NEGLIGENCE BY REDBACK, SHALL IN ALL EVENTS BE LIMITED TO RETURN OF THE AMOUNTS ACTUALLY PAID TO REDBACK FOR THE DEFECTIVE HARDWARE OR SOFTWARE, LESS DEPRECIATION OF SUCH AMOUNTS LINEARLY OVER A THREE-YEAR PERIOD, WHICH THE PARTIES AGREE CONSTITUTES A REASONABLE RATE OF DEPRECIATION.

FCC Notice

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Increase the separation between equipment and receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio or television technician for help.

1. MODIFICATIONS

The FCC requires the user to be notified that any changes or modifications made to this device that are not expressly approved by Redback could void the user's authority to operate the equipment.

2. CABLES

Connection to this device must be made with shielded cables with metallic RF/EMI connector hoods to maintain compliance with FCC Rules and Regulations.

3. OPERATING CONDITIONS

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

4. POWER CORD SET REQUIREMENTS

The power cord set used with the System must meet the requirements of the country, whether it is 100-120 or 220-264 VAC.

U.S. and Canada. The cord set must be UL Listed and CSA Certified.

5. SAFETY NOTICES

- a. Laser Equipment:

CAUTION! USE OF CONTROLS OR ADJUSTMENTS OF PERFORMANCE OR PROCEDURES OTHER THAN THOSE SPECIFIED HEREIN MAY RESULT IN HAZARDOUS RADIATION EXPOSURE.

- b. Lithium Battery:

It is recommended that, when required, Redback replace the lithium battery.

CAUTION! DANGER OF EXPLOSION IF BATTERY IS INCORRECTLY REPLACED. REPLACE ONLY WITH THE SAME OR EQUIVALENT TYPE IS RECOMMENDED BY THE MANUFACTURER'S INSTRUCTIONS.

Year 2000 (Y2K) Compliance

The SMS 1000 and SMS 500 are Year 2000 (Y2K) Compliant. This means that the SMS 1000 and SMS 500 accurately process date/time data (including, but not limited to, calculating, comparing, and sequencing) from, into, and between the twentieth and twenty-first centuries, and the years 1999 and 2000 including the year 2000 leap-year calculations. Furthermore, when used in combination with other information technology, the SMS 1000 and SMS 500 accurately process date/time data to the extent other information technology properly exchanges date/time data with it.

Copyright © 1999, Redback Networks, Inc. All Rights Reserved.

Redback and the Subscriber Management System are trademarks of Redback Networks, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks, or registered service marks of their respective owners.

Table of Contents

About This Manual

| | |
|----------------------------|------|
| Objectives | xiii |
| Related Publications | xiii |
| Intended Audience | xiii |
| Organization | xiv |
| Conventions | xiv |
| Commands | xiv |
| Examples | xv |

Chapter 1: System Overview

| | |
|------------------------------|-----|
| The Redback Solution | 1-1 |
| AOS Functions | 1-1 |
| AOS Features | 1-2 |
| AOS Applications | 1-3 |
| AOS Concepts | 1-3 |
| Contexts | 1-4 |
| Interfaces | 1-5 |
| Subscribers | 1-5 |
| Ports and Circuits | 1-5 |
| Bindings | 1-5 |
| Configuration Overview | 1-6 |

Chapter 2: Introduction to the User Interface

| | |
|--|-----|
| Modes | 2-1 |
| Auto-More | 2-5 |
| Command-Line History and Command Editing | 2-5 |

Chapter 3: Loading and Maintaining the System

| | |
|--|-----|
| Upgrading the System Image | 3-1 |
| Using the Flash File System | 3-1 |
| Using the PCMCIA Flash File System | 3-1 |
| Managing System Images | 3-2 |
| Managing Configurations | 3-3 |
| Network Loading the System | 3-4 |
| Hot-Swapping a Module | 3-6 |

| | |
|---------------------------------------|-----|
| Preparing for Module Extraction | 3-7 |
| Replacing the Module | 3-7 |
| Configuring the New Module | 3-7 |

Chapter 4: Managing the System

| | |
|---|------|
| Console and Telnet Login | 4-1 |
| Configuring Telnet | 4-2 |
| Local Context | 4-2 |
| System Log | 4-3 |
| Configuring SNMPv1 and SNMPv2c | 4-5 |
| Configuration Tasks | 4-5 |
| Enable the SNMP Server | 4-5 |
| Configure SNMP Views | 4-5 |
| Configure SNMP Communities | 4-6 |
| Configure SNMP Traps | 4-6 |
| Configuration Examples | 4-6 |
| Configuring SNMPv3 | 4-7 |
| Overview | 4-7 |
| Security Considerations | 4-7 |
| Configuration Tasks | 4-8 |
| Enable the SNMP Server | 4-8 |
| Configure the Local Engine-ID | 4-8 |
| Configure SNMP Views | 4-8 |
| Configure SNMP Groups | 4-9 |
| Configure SNMP Users | 4-9 |
| Configure SNMP Notifications | 4-9 |
| Configuration Examples | 4-10 |
| Supported MIBs, Traps, and Events | 4-10 |
| Configuring RMON | 4-11 |
| Configuration Tasks | 4-12 |
| Configuring RMON Alarms | 4-12 |
| Configuring RMON Events | 4-12 |
| Configuration Examples | 4-12 |
| Bulk Statistics | 4-13 |
| Understanding the Process | 4-13 |
| Working with Schemas | 4-13 |
| Configuring Bulkstats | 4-15 |
| Configuration Example | 4-16 |
| Web-Based Management | 4-16 |

Chapter 5: Configuring the System

| | |
|--|-----|
| Configuring Global Parameters | 5-1 |
| Configuring Interfaces and Ports | 5-2 |
| Loopback Interfaces | 5-3 |
| Configuring Secondary IP Addresses | 5-4 |
| Configuring Subscribers and PPP | 5-4 |
| Static Binding for PPP-Encapsulated Circuits | 5-6 |
| PPP Oversubscription | 5-7 |
| PPP Idle and Absolute Timeout | 5-7 |

| | |
|--|------|
| Configuring PPPoE | 5-8 |
| PPPoE for Bridge-Encapsulated ATM and Frame Relay Circuits | 5-8 |
| PPPoE for Physical Ethernet Ports | 5-9 |
| Advertising a List of Services | 5-9 |
| Sending MOTMs to Subscribers | 5-10 |
| Pointing the Subscriber's Browser to a URL | 5-11 |
| Configuring DHCP Support | 5-11 |
| Nonvolatile Storage of DHCP Secured ARP State | 5-13 |
| Overview of DHCP and Secured ARP | 5-13 |
| System Requirements | 5-14 |
| Configuration Tasks | 5-14 |
| Format the SRAM PCMCIA Card | 5-14 |
| Enable DHCP Preserve-State | 5-15 |
| Configuration Examples | 5-15 |
| Configuring DNS | 5-15 |
| Overview | 5-15 |
| Configuration Tasks | 5-15 |
| Enable DNS | 5-16 |
| Provide a Domain Name | 5-16 |
| Configure a Connection to a DNS Server | 5-16 |
| Place Static Entries in the Local Host Table | 5-16 |
| Monitor DNS | 5-16 |
| Troubleshoot DNS | 5-16 |
| Configuration Examples | 5-17 |
| Configuring Custom Formats for Structured Usernames | 5-17 |
| Implications of Customizing Username Formats | 5-17 |
| Configuration Tasks | 5-18 |
| Define One or More Custom Formats | 5-18 |
| Designate the Default Domain and Define its Behavior | 5-18 |
| Configuration Examples | 5-19 |
| Configuring NTP | 5-19 |
| Overview | 5-20 |
| Configuration Tasks | 5-20 |
| Configure the SMS to Synchronize to an NTP Server | 5-20 |
| Set NTP Parameters | 5-20 |
| Monitor NTP | 5-21 |
| Troubleshoot NTP | 5-21 |
| Configuration Examples | 5-21 |
| IP Routing Protocols Overview | 5-21 |
| IGPs Versus EGPs | 5-22 |
| Routing Table | 5-22 |
| Forwarding Table | 5-22 |
| Route Precedences | 5-22 |
| Active Route Selection | 5-22 |
| Configuring BGP | 5-23 |
| Redback's Implementation | 5-23 |
| Overview | 5-23 |
| Aggregate Routes | 5-24 |
| BGP Messages | 5-24 |
| Path Attributes | 5-26 |

| | |
|--|------|
| Configuration Tasks | 5-26 |
| Enable BGP Routing | 5-27 |
| Define Global BGP Parameters | 5-27 |
| Configure BGP Group Characteristics | 5-28 |
| Configure BGP Peer Characteristics | 5-29 |
| Display BGP Information | 5-30 |
| Troubleshoot BGP | 5-31 |
| Configuration Examples | 5-31 |
| Configuring OSPF | 5-31 |
| Redback's Implementation | 5-31 |
| Overview | 5-32 |
| OSPF Hierarchy | 5-32 |
| AS External Routes | 5-33 |
| Router Functions | 5-34 |
| Link-State Databases | 5-34 |
| Packet Types | 5-35 |
| SPF Calculations | 5-36 |
| OSPF Routes | 5-36 |
| Configuration Tasks | 5-36 |
| Enable OSPF Routing | 5-36 |
| Define Global OSPF Parameters | 5-37 |
| Configure OSPF Interface Characteristics | 5-38 |
| Display OSPF Information | 5-38 |
| Troubleshoot OSPF | 5-39 |
| Configuration Examples | 5-39 |
| Configuring RIP | 5-40 |
| Configuring IP Static Routes | 5-40 |
| Configuring Routing Policies | 5-41 |
| Overview | 5-41 |
| Configuration Tasks | 5-42 |
| Configure BGP AS Path Access Lists | 5-42 |
| Configure BGP Community Lists | 5-42 |
| Configure Route Access Lists | 5-43 |
| Create Route Maps | 5-43 |
| Determine the Route Map Match Criteria | 5-43 |
| Determine the Route Map Set Actions | 5-44 |
| Configuration Examples | 5-45 |
| Configuring IGMP Proxy | 5-46 |
| Redback's Implementation | 5-46 |
| Overview | 5-47 |
| Configuration Tasks | 5-49 |
| Enable IGMP Proxy (and Limit the Number of Groups Per Context) | 5-50 |
| Designate the IGMP Proxy Router Interface | 5-50 |
| Add or Remove Circuits in Multicast Groups | 5-51 |
| Limit the Number of Groups a Subscriber Can Join | 5-51 |
| Use Access Control Lists to Restrict IGMP Query Types | 5-51 |
| Tune IGMP Interface Parameters | 5-52 |
| Enable Multicast Counters | 5-52 |
| Show IGMP Proxy Statistics | 5-53 |
| Run IGMP Proxy Debug | 5-53 |

| | |
|--|------|
| Configuration Examples | 5-53 |
| Configuring ATM PVCs | 5-54 |
| RFC 1483 Bridged Encapsulation and Secured ARP | 5-56 |
| Auto-Detection for Encapsulation Type | 5-58 |
| Multiple Encapsulations on a Single Circuit | 5-59 |
| Create the PVC | 5-59 |
| Specify the Bindings for the Multiple Encapsulations | 5-59 |
| Configuration Example | 5-60 |
| Configuring ATM VP Shaping | 5-60 |
| Configuration Tasks | 5-61 |
| Configure an ATM Profile for the Virtual Path | 5-61 |
| Configure ATM Profiles for the Virtual Circuits | 5-62 |
| Create the Virtual Path | 5-62 |
| Create Virtual Circuits | 5-62 |
| Configuration Examples | 5-62 |
| Configuring 802.1Q to Bridge 1483 Interworking | 5-63 |
| Configuring SONET APS | 5-64 |
| Redback's Implementation | 5-64 |
| Overview | 5-65 |
| Configuration Tasks | 5-65 |
| Create an APS Group | 5-65 |
| Designate the Working and Protect Ports | 5-66 |
| Modify the BER Threshold for Switchovers | 5-66 |
| Override Port Settings | 5-66 |
| Show APS Statistics | 5-67 |
| Run APS Debug | 5-67 |
| Configuration Examples | 5-67 |
| Configuring IMA | 5-67 |
| Configuration Tasks | 5-67 |
| Create an IMA Group | 5-68 |
| Define the Constituent Ports | 5-68 |
| Configure Optional IMA Group Parameters | 5-68 |
| Configure IMA Ports | 5-70 |
| Configure IMA PVCs | 5-70 |
| Enable the IMA Group | 5-70 |
| Configuration Examples | 5-71 |
| Configuring Channelized DS-3 I/O Modules | 5-71 |
| Configuring Alternate HDLC Encapsulations | 5-73 |
| Configuring Frame Relay PVCs | 5-74 |
| Auto-Detection for Encapsulation Type | 5-76 |
| Multiple Encapsulations on a Single Circuit | 5-76 |
| Create the PVC | 5-76 |
| Specify the Bindings for the Multiple Encapsulations | 5-77 |
| Configuration Example | 5-77 |
| Troubleshooting the Configuration | 5-77 |
| Configuring Bypasses | 5-78 |
| Configuring L2TP | 5-79 |
| Dynamic Tunnel Selection | 5-80 |
| Configuring a LAC | 5-80 |
| Configuring an LNS | 5-82 |

| | |
|--|-------|
| Configuring Tunnels over PVCs | 5-83 |
| Configuring Tunnel Switching | 5-84 |
| RADIUS One-Pass Feature | 5-86 |
| DNIS-Based Tunnel Switching | 5-86 |
| RADIUS Support for DNIS-Based Tunnel Switching | 5-87 |
| Configuring L2TP Groups | 5-88 |
| RADIUS Considerations for Configuring L2TP Groups | 5-89 |
| Servers That Do Not Support Tunnel Extensions | 5-90 |
| Servers That Do Support Tunnel Extensions | 5-91 |
| Making Configuration Changes | 5-92 |
| Changing L2TP Default Settings | 5-92 |
| Configuring Ethernet over L2TP | 5-93 |
| Overview | 5-93 |
| Configuration Tasks on the LAC Side | 5-94 |
| Identify the Ethernet Ports or Bridge-Encapsulated Circuits | 5-94 |
| Bind the Ports or Bridge-Encapsulated Circuits to the Peers | 5-94 |
| Enable Ethernet Sessions Retry over L2TP | 5-95 |
| Configuration Tasks on the LNS Side | 5-95 |
| Determine How Subscribers Will Be Terminated | 5-95 |
| Bind the Sessions | 5-95 |
| Configuration Examples | 5-96 |
| Configuring L2F | 5-96 |
| Overview | 5-96 |
| Configuration Tasks | 5-97 |
| Create L2F Peers | 5-97 |
| Configure Peers as NAS or Home Gateway | 5-97 |
| Establish Aliases for the Peers | 5-98 |
| Configure the Parameters | 5-98 |
| Create the Circuits | 5-99 |
| Bind the Circuits to the Peers | 5-99 |
| Configuration Examples | 5-99 |
| Configuring Bridges | 5-100 |
| Configuring RADIUS | 5-103 |
| Global AAA | 5-104 |
| Context Assignment with Global AAA | 5-105 |
| Two-Stage Accounting | 5-105 |
| RADIUS Redundancy and Load Balancing | 5-106 |
| Separate RADIUS Authentication and Accounting Servers | 5-106 |
| Configuration of Circuits via RADIUS | 5-107 |
| Specify the Means by Which Circuits Are Defined | 5-107 |
| Specify That Circuit Creation Is to Be Done via AAA | 5-107 |
| Set Up the Range of VPI:VCI Values | 5-107 |
| Add a Prefix for Use in Constructing the User-Name Attribute | 5-108 |
| Configuration Example | 5-108 |
| Auto-Subscriber Function | 5-108 |
| Locally Managed IP Address Pools | 5-109 |
| Support for Tagged Attributes | 5-110 |
| Combining RADIUS Features | 5-110 |
| Configuring Access Control Lists | 5-111 |
| Access Control List Examples | 5-112 |

| | |
|--|-------|
| Example 1 | 5-113 |
| Example 2 | 5-114 |
| Example 3 | 5-115 |
| Example 4 | 5-116 |
| Example 5 | 5-117 |
| Bridge Access Control Lists | 5-118 |
| Administrative Access Control Lists | 5-118 |
| Configuring Service Access Lists | 5-120 |
| Characteristics and Behavior of Service Access Lists | 5-120 |
| Configuration Tasks | 5-121 |
| Map Out the Goals of the List | 5-121 |
| Create the Service Access List | 5-122 |
| Create the Statements in the List | 5-122 |
| Display the Completed List | 5-122 |
| Apply the Service Access List | 5-123 |
| Configuration Examples | 5-123 |
| Configuring Traffic Contracts | 5-124 |
| Configuring Multiple Contexts | 5-126 |
| Miscellaneous Features | 5-129 |
| IP Source Address-Verification | 5-129 |
| C-BIT Support on Clear Channel DS-3 Modules | 5-129 |
| Clear Counters | 5-129 |

Appendix A: Sample System Configuration File

Appendix B: Binding and Encapsulation Types

| | |
|--|-----|
| ATM Circuits | B-1 |
| Frame Relay Circuits | B-2 |
| HDLC-Oriented Ports and Channels | B-2 |
| Ethernet Ports | B-3 |

Appendix C: Traffic Shaping

| | |
|---|-----|
| Unspecified Bit Rate (UBR) | C-1 |
| Constant Bit Rate (CBR) | C-1 |
| Realtime Variable Bit Rate (VBR-rt) | C-2 |
| Nonrealtime Variable Bit Rate (VBR-nrt) | C-2 |
| Guaranteed Frame Rate (GFR) | C-2 |

Appendix D: Troubleshooting

Appendix E: RADIUS Attributes

Appendix F: L2TP Attribute Value Pairs

Index

Once the default settings have been changed, the new values will be applied to any new peer that is created unless the values are changed in the configuration for an individual peer.

Configuring Ethernet over L2TP

This section describes how to configure L2TP tunnels to carry Ethernet-encapsulated PPPoE sessions. Before configuring your system for Ethernet over L2TP, be sure to read the preceding section called “Configuring L2TP.”

By allowing Ethernet sessions over L2TP tunnels, AOS is able to provide the LNS full control over the advertisement of services. The following sections are included:


- “Overview”
- “Configuration Tasks on the LAC Side”
- “Configuration Tasks on the LNS Side”
- “Configuration Examples”

For a complete description of the commands related to Ethernet over L2TP, see the *Access Operating System (AOS) Command Reference*.

Overview

The AOS implementation of Ethernet over L2TP allows Ethernet sessions to be tunneled intact to the LNS. Since Ethernet connectivity is required for advertisement of services, this is a significant advantage for the LNS. Figure 5-15 shows the relationship of protocols/encapsulations between a LAC and an LNS in the three types of sessions that might be tunneled in this fashion: PPP over Ethernet (PPPoE), IP over Ethernet, and Bridging.

Figure 5-15 Protocol Stack When Tunneling Ethernet over L2TP



It is important to note that if more than one Ethernet session is tunneled from one peer and bound to the same interface on the LNS, AOS can not use ARP to resolve the IP address to a physical/MAC address. As an alternative, you can use DHCP with secured ARP as a way to map IP addresses to physical MAC addresses.

Configuration Tasks on the LAC Side

To configure Ethernet over L2TP on the LAC side, you must first set up the L2TP peers according to the instructions in the previous section, “Configuring L2TP.” Then, perform the tasks in the following sections:

- “Identify the Ethernet Ports or Bridge-Encapsulated Circuits”
- “Bind the Ports or Bridge-Encapsulated Circuits to the Peers”
- “Enable Ethernet Sessions Retry over L2TP”

Identify the Ethernet Ports or Bridge-Encapsulated Circuits

The first step is to decide which Ethernet ports or bridge-encapsulated circuits you want tunneled over L2TP. This is necessary because you will be “hard” binding them to L2TP peers.

Bind the Ports or Bridge-Encapsulated Circuits to the Peers

To bind a port or circuit to an L2TP peer, enter the following command in port, circuit, or HDLC channel configuration mode as appropriate:

```
bind session peer-name context
```

where *peer-name* is the name of the L2TP peer to which the circuit or port is to be bound and *context* is the context in which that peer exists. If you are binding an Ethernet port, the bind session command puts the port into “promiscuous mode” which means that it will ignore MAC addresses and tunnel everything to the LNS. The concept of promiscuous mode is implicit for Bridged 1483 and Bridged 1490 encapsulated circuits.

Enable Ethernet Sessions Retry over L2TP

To enable the creation of Ethernet sessions over L2TP, enter the following command in context configuration mode:

```
aaa authentication re-try minutes
```

where *minutes* is the number of minutes the system is to wait before re-attempting to connect after failure to establish a session to the tunnel peer. By default, no further attempts are made once an attempt to create a session has failed. No attempt is made to create a connection until data begins to come through over the circuit/port.

Configuration Tasks on the LNS Side

To configure Ethernet over L2TP from the LNS side, you must first set up the L2TP peers as described in the previous section, “Configuring L2TP.” Then, perform the tasks in the following sections:

- “Determine How Subscribers Will Be Terminated”
- “Bind the Sessions”

Determine How Subscribers Will Be Terminated

Subscribers can be terminated in one of two ways: IP over Ethernet or PPPoE. These two encapsulations are mutually exclusive and apply to all Ethernet-encapsulated sessions from the peer. This decision is made on the LNS side because the LAC is intended to send everything, without evaluation.

If the client is using PPPoE, configure the peer as such by entering the following command in L2TP configuration mode:

```
ethernet encapsulation ppp over-ethernet
```

If the client is using IP over Ethernet, the default setting for this command (**ppp**) is what you want.

Bind the Sessions

To bind a session to a PPPoE client, enter the following command in L2TP configuration mode:

```
ethernet session auth {pap | chap | chap pap} [maximum sessions] [context name | service-group name]}
```

where **pap**, **chap**, and **chap pap** are authentication method choices, the **maximum sessions** construct allows you to limit the number of PPPoE sessions allowed per L2TP session, the **context name** construct allows you to restrict the Ethernet-encapsulated PPPoE sessions to the named context, and the

Configuring L2F

service-group *name* construct allows you to limit the services available to those permitted by the named service access list. If the **peer** is not first encapsulated as PPPoE (with the **ethernet encapsulation ppp over-ethernet** command), the **auth** construct is not available on the command line.

To bind a session to an IP over Ethernet client, enter the following command in L2TP configuration mode:

ethernet session interface *interface context*

where *interface* is the name of the interface to which the Ethernet session is to be bound and *context* is the name of the context in which the interface exists.

Configuration Examples

The following example shows configuring an L2TP peer to terminate subscribers as PPPoE and bind the Ethernet sessions to the peer with CHAP PAP:

```
[local] RedBack (config-ctx) #l2tp-peer name lnsmain media pvc
[local] RedBack (config-l2tp) #ethernet encapsulation ppp over-ethernet
[local] RedBack (config-l2tp) #ethernet session auth pap
```

Configuring L2F

This section describes AOS' ability to interoperate with legacy systems that are implementing Cisco's Layer 2 Forwarding (L2F) protocol. L2F supports the creation of secure virtual private dial-up networks over the Internet and is one of the predecessors to L2TP.

The following sections are included:

- "Overview"
- "Configuration Tasks"
- "Configuration Examples"

For a complete description of the commands related to L2F, see the *Access Operating System (AOS) Command Reference*.

Overview

The AOS implementation of L2F supports the following:

- Both Network Access Server (NAS) and home gateway functions. Consistent with the limitations of the L2F protocol, a peer may function as one or the other, but not both.
- Tunnel switching between L2F tunnels and between L2F and L2TP tunnels.
- UDP/IP tunnel encapsulation.
- A tunnel may be defined in one context, while the sessions within that tunnel may be terminated or may be further tunneled (tunnel switch) in any contexts.
- L2F tunnel configurations can be configured locally (in the AOS configuration file) or they can be served by RADIUS.

Access Operating System (AOS) Command Reference

Release Number or Date
Part Number 220-0123-01

Redback
NETWORKS

Corporate Headquarters
Redback Networks, Inc.
1389 Moffett Park Drive
Sunnyvale, CA 94089-1134
USA
<http://www.redback.com>
Tel: 408-548-3500

Rights and Restrictions

All statements, specifications, recommendations, and technical information contained are current or planned as of the date of publication of this document. They are reliable as of the time of this writing and are presented without warranty of any kind, expressed or implied. In an effort to continuously improve the product and add features, Redback Networks, Inc. ("Redback") reserves the right to change any specifications contained in this document without prior notice of any kind.

Redback shall not be liable for technical or editorial errors or omissions which may occur in this document. Redback shall not be liable for any indirect, special, incidental or consequential damages resulting from the furnishing, performance, or use of this document.

The following information is for FCC compliance of Class A devices: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio-frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case users will be required to correct the interference at their own expense.

Any modifications to this product not authorized by Redback could void the FCC approval and negate the user's authority to operate the product.

Limited Hardware Warranty and Disclaimer

Limited Warranty. Redback warrants to the original purchaser of the product ("Purchaser") only that the hardware sold hereunder shall be free of defects in material and workmanship and shall perform, under normal use and circumstances, in accordance with Redback's published specifications for a period of ninety (90) days from the shipment date. In the event that Redback receives notice from Purchaser during the warranty period that any hardware does not conform to its warranty, Redback shall, at its sole option (and as Purchaser's sole remedy), either repair or replace the non-conforming hardware, or refund the purchase price of such unit. Hardware replaced under the terms of any such warranty may be refurbished or new equipment substituted at Redback's option. This warranty is the only warranty made by Redback with respect to the hardware delivered hereunder and may be modified, amended or supplemented only by a written instrument signed by a duly authorized officer of Redback and accepted by Purchaser.

Procedures. A hardware item may only be returned with the prior written approval of Redback. Any such approval shall reference a return material authorization number issued by authorized Redback service personnel. Transportation costs, if any, incurred in connection with the return of a defective item to Redback shall be borne by Purchaser. Any transportation costs incurred in connection with the re-delivery of a repaired or replaced item to Purchaser shall be borne by Redback; provided that, such costs shall be borne by Purchaser if Redback reasonably determines that the item is not defective. If Redback determines, in its sole discretion, that the allegedly defective item is not covered by the terms of the warranty provided hereunder or that a warranty claim is made after the warranty period, the cost of repair by Redback, including all shipping expenses, shall be reimbursed by Purchaser.

Exclusions. The foregoing warranties and remedies are for Purchaser's exclusive benefit and are non-transferable. The foregoing warranties do not apply to any hardware which (1) has been altered, except as authorized by Redback, (2) has not been installed, operated, repaired, or maintained in accordance with any installation, handling, maintenance, or operating instructions supplied by Redback, (3) has been subjected to unusual physical or electrical stress, misuse, negligence, or accident (4) is used in ultrahazardous activities, (5) has been damaged or rendered unserviceable by installation or use outside of environmental specifications, or (6) has been exported from the original country of destination. In no event does Redback warrant that Purchaser will be able to operate its networks without problems or interruptions.

Third Party Products. Where a product not manufactured by Redback is sold by Redback hereunder to complete an order, the warranty coverage on that product is limited to its original manufacturer's warranty to the Purchaser, if any.

THE LIMITED WARRANTIES SET FORTH ABOVE ARE IN LIEU OF ALL OTHER WARRANTIES, WHETHER EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE, AND REDBACK SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. REDBACK DOES NOT WARRANT THAT THE PRODUCTS WILL MEET PURCHASER'S REQUIREMENTS OR THAT THE OPERATION OF THE PRODUCTS WILL BE UNINTERRUPTED OR ERROR FREE.

Software License Agreement

CAREFULLY READ THE FOLLOWING TERMS AND CONDITIONS. BY INSTALLING AND USING SOFTWARE INCLUDED WITH THE REDBACK PRODUCTS, YOU ARE AGREEING TO BE BOUND BY THESE TERMS AND CONDITIONS. IF YOU DO NOT AGREE TO THESE TERMS AND CONDITIONS, DO NOT USE THE REDBACK PRODUCTS.

1. SOFTWARE

The software covered by this license agreement includes (i) all Redback proprietary software provided with the product, whether provided on magnetic media or embedded in the product as firmware, and (ii) any third party owned software licensed to Redback and provided by Redback with the product (jointly, the "Software"). The following third party Software may be included with your product and is subject to this software license agreement:

- a. SNMP Monolithic Agent. Copyright © 1992-1998 SNMP Research International, Inc. All rights reserved.
 - b. VxWorks. Copyright © 1984-1998 Wind River Systems, Inc. All rights reserved.
 - c. The Redback Networks adaptation and implementation of the UDP and TCP protocols developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. Copyright © 1982, 1986, 1988, 1990, 1993, 1995 The Regents of the University of California. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: (1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. (2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. (3) All advertising materials mentioning features or use of this software must display the following acknowledgment: This product includes software developed by the University of California, Berkeley and its contributors. (4) Neither the name of the University nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.
 - d. Point-to-Point Protocol (PPP). Copyright © 1989, Carnegie-Mellon University. All rights reserved. The name of the University may not be used to endorse or promote products derived from this software without specific prior written permission.
-

e. Dynamic Host Configuration Protocol (DHCP) developed by The Internet Software Consortium. Copyright © 1997, 1998. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met: (1) Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer. (2) Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution. (3) Neither the name of The Internet Software Consortium nor the names of its contributors may be used to endorse or promote products derived from this software without specific prior written permission.

2. LICENSE

Redback hereby grants to the original end user of the products ("Licensee") only, and Licensee hereby accepts, a personal, non-transferable, non-exclusive license to use the Software and related product documentation (the "Documentation") in accordance with the terms and conditions of this agreement.

Licensee may use the Software solely with the original Redback products or system with which it is provided (the "System"). Licensee may not transfer the Software to or use the Software on any equipment other than the System, whether or not such other equipment shall have been manufactured by Redback. This license shall expire upon sale of the System by Licensee.

Licensee agrees not to make any copies of the Software or the Documentation, in whole or in part, other than one permitted copy of the Software and Documentation which Licensee may maintain for archival purposes only. Licensee agrees not to modify, translate, reverse engineer, de-compile, disassemble, or create derivative works based on the Software, except to the extent that the foregoing may not be prohibited by applicable law.

Licensee agrees to take reasonable steps to safeguard copies of the Software against disclosure, copying or use by unauthorized persons, and to take reasonable steps to ensure that the provisions of this license are not violated by Licensee's employees or agents.

3. TITLE

Licensee acknowledges and agrees that all right, title and interest in and to the Software and Documentation, including all intellectual property rights therein, shall remain the property of Redback or its suppliers, subject only to the limited license to use granted to Licensee hereunder. This license is not a sale and does not transfer to Licensee any title or ownership in or to the Software or the Documentation or any patent, copyright, trade secret, trade name, trademark or other proprietary or intellectual property rights related thereto.

4. NONTRANSFERABILITY

Licensee may not rent, transfer, assign, sublicense or grant any rights in the Software or Documentation, in full or in part, to any other person or entity.

5. NO SOFTWARE WARRANTY

Redback warrants to Licensee only that the media on which the Software is recorded shall be free from defects in materials and workmanship under normal use for a period of ninety (90) days from the date of shipment by Redback. Licensee's sole and exclusive remedy, and Redback's sole and exclusive liability, shall be replacement of the media in accordance with this limited warranty.

THE SOFTWARE IS PROVIDED "AS IS." REDBACK EXPRESSLY DISCLAIMS AND NEGATES ALL WARRANTIES FOR THE SOFTWARE, WHETHER EXPRESSED, IMPLIED, STATUTORY OR OTHERWISE, AND REDBACK SPECIFICALLY DISCLAIMS ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, NON-INFRINGEMENT OF INTELLECTUAL PROPERTY OR OTHER VIOLATION OF RIGHTS. REDBACK DOES NOT WARRANT THAT THE SOFTWARE WILL MEET PURCHASER'S REQUIREMENTS OR THAT THE OPERATION OF THE SOFTWARE WILL BE UNINTERRUPTED OR ERROR FREE.

Some states or countries do not allow exclusion or limitation of incidental or consequential damages or limitation on how long an implied warranty lasts, so the above limitations or exclusions may not apply to Licensee. This warranty gives Licensee specific legal rights and Licensee may also have other rights, which vary from state to state or country to country.

6. TERMINATION

This agreement shall continue in effect until terminated hereunder. This agreement shall terminate automatically on Licensee's failure to comply with any of the restrictions and provisions herein, including without limitation any attempt to transfer this license. Upon any termination of this agreement, Licensee agrees promptly to destroy or return to Redback all copies of the Software and Documentation, including without limitation all original and archival copies thereof. No refunds shall be given for such returned materials. Notwithstanding any termination of this License, the rights and obligations set forth in Sections 3 (Title), 4 (Non-transferability), 5 (Limited Software Warranty), 6 (Termination), 7 (Limitation of Liability) and 8 (Miscellaneous) shall survive such termination.

7. U.S. GOVERNMENT RESTRICTED RIGHTS

The Software and Documentation are provided with Restricted Rights. Use, duplication, or disclosure by the Government is subject to restrictions as set forth in subparagraph (c) (1) (ii) of The Rights in Technical Data and Computer Software clause at DFARS 252.227-7013 or subparagraphs (c) (1) and (2) of the Commercial Computer Software—Restricted Rights at 48 CFR 52.227-19, as applicable. Manufacturer is Redback Networks, Inc., 1389 Moffett Park Drive, Sunnyvale, California 94089.

8. MISCELLANEOUS

a. Licensee may not assign or transfer any of its rights or delegate any of its obligations under this agreement. Any attempted assignment or delegation by Licensee shall be null and void.

b. No delay, failure or waiver by either party to exercise any right or remedy under this agreement shall operate to limit, preclude, cancel or waive any exercise of such right or remedy or the exercise of any other right or remedy.

c. This agreement shall be governed by and construed in accordance with the laws of the State of California without regard to conflict of laws principles and without regard to the 1980 U.N. Convention on Contracts for the International Sale of Goods. The federal and state courts of California shall have exclusive jurisdiction and venue to adjudicate any dispute arising out of this agreement, and Licensee expressly consents to (i) the personal jurisdiction of the state and federal courts of California and (ii) service of process being effected upon it by registered mail sent to the Licensee.

d. If any provision in this agreement shall be found or be held to be invalid or unenforceable in any jurisdiction in which this agreement is being performed, then the meaning of said provision shall be construed, to the extent feasible, so as to render the provision enforceable, and if no feasible interpretation would save such provision, it shall be severed from the remainder of this agreement, which shall remain in full force and effect. In such event, the parties shall negotiate, in good faith, a substitute, valid and enforceable provision, which most nearly effects the parties' intent in entering into this agreement.

e. This software license agreement incorporates the General Limitation of Liability and Damages provisions set forth below.

f. This agreement constitutes the entire agreement between Licensee and Redback with respect to the subject matter of this agreement and shall supersede all prior oral or written understandings, communications or advertising. This agreement may be amended or modified only in writing signed by both parties.

Limitation of Liability and Damages

THE FOLLOWING LIMITATION OF LIABILITY AND DAMAGES APPLIES TO ALL HARDWARE, SOFTWARE AND DOCUMENTATION SOLD, LICENSED OR OTHERWISE DISTRIBUTED BY REDBACK OR ITS RESELLERS.

IN NO EVENT SHALL REDBACK, ITS SUPPLIERS OR ITS DISTRIBUTORS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGE, INCLUDING WITHOUT LIMITATION LOSS OF DATA, LOST PROFITS OR COST OF COVER, ARISING FROM THE USE OF THE HARDWARE, SOFTWARE OR DOCUMENTATION OR ANY DEFECT IN THE HARDWARE, SOFTWARE OR DOCUMENTATION, HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY. THIS LIMITATION SHALL APPLY EVEN IF REDBACK, ITS SUPPLIERS OR ITS DISTRIBUTOR SHALL HAVE BEEN ADVISED OF THE POSSIBILITY OF ANY SUCH DAMAGE. IN PARTICULAR, BUT WITHOUT LIMITATION, REDBACK, ITS SUPPLIERS AND ITS DISTRIBUTORS SHALL HAVE NO LIABILITY FOR THE LOSS OF ANY INFORMATION STORED OR COMMUNICATED OR ATTEMPTED TO BE STORED OR COMMUNICATED WITHIN ANY REDBACK SYSTEM USING THE HARDWARE OR SOFTWARE.

THE MAXIMUM AGGREGATE LIABILITY OF REDBACK AND ITS SUPPLIERS FOR ANY CLAIM ARISING OUT OF USE OF THE HARDWARE, SOFTWARE OR DOCUMENTATION OR ANY DEFECT IN THE HARDWARE, SOFTWARE OR DOCUMENTATION, ON ANY AND ALL THEORIES OF LIABILITY, INCLUDING WITHOUT LIMITATION NEGLIGENCE BY REDBACK, SHALL IN ALL EVENTS BE LIMITED TO RETURN OF THE AMOUNTS ACTUALLY PAID TO REDBACK FOR THE DEFECTIVE HARDWARE OR SOFTWARE, LESS DEPRECIATION OF SUCH AMOUNTS LINEARLY OVER A THREE-YEAR PERIOD, WHICH THE PARTIES AGREE CONSTITUTES A REASONABLE RATE OF DEPRECIATION.

FCC Notice

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. This equipment generates, uses, and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Increase the separation between equipment and receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio or television technician for help.

1. MODIFICATIONS

The FCC requires the user to be notified that any changes or modifications made to this device that are not expressly approved by Redback could void the user's authority to operate the equipment.

2. CABLES

Connection to this device must be made with shielded cables with metallic RF/EMI connector hoods to maintain compliance with FCC Rules and Regulations.

3. OPERATING CONDITIONS

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

4. POWER CORD SET REQUIREMENTS

The power cord set used with the System must meet the requirements of the country, whether it is 100-120 or 220-264 VAC.

U.S. and Canada. The cord set must be UL Listed and CSA Certified.

5. SAFETY NOTICES

a. Laser Equipment:

CAUTION! USE OF CONTROLS OR ADJUSTMENTS OF PERFORMANCE OR PROCEDURES OTHER THAN THOSE SPECIFIED HEREIN MAY RESULT IN HAZARDOUS RADIATION EXPOSURE.

b. Lithium Battery:

It is recommended that, when required, Redback replace the lithium battery.

CAUTION! DANGER OF EXPLOSION IF BATTERY IS INCORRECTLY REPLACED. REPLACE ONLY WITH THE SAME OR EQUIVALENT TYPE IS RECOMMENDED BY THE MANUFACTURER'S INSTRUCTIONS.

Year 2000 (Y2K) Compliance

The SMS 1000 and SMS 500 are Year 2000 (Y2K) Compliant. This means that the SMS 1000 and SMS 500 accurately process date/time data (including, but not limited to, calculating, comparing, and sequencing) from, into, and between the twentieth and twenty-first centuries, and the years 1999 and 2000 including the year 2000 leap-year calculations. Furthermore, when used in combination with other information technology, the SMS 1000 and SMS 500 accurately process date/time data to the extent other information technology properly exchanges date/time data with it.

Copyright © 1999, Redback Networks, Inc. All Rights Reserved.

Redback and the Subscriber Management System are trademarks of Redback Networks, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks, or registered service marks of their respective owners.

All statements, specifications, recommendations, and technical information contained are current or planned as of the date of publication of this document. They are reliable as of the time of this writing and are presented without warranty of any kind, expressed or implied. In an effort to continuously improve the product and add features, Redback Networks, Inc. ("Redback") reserves the right to change any specifications contained in this document without prior notice of any kind.

Redback shall not be liable for technical or editorial errors or omissions which may occur in this document. Redback shall not be liable for any indirect, special, incidental or consequential damages resulting from the furnishing, performance, or use of this document.

Copyright © 2000, Redback Networks, Inc. All Rights Reserved.

Redback and the Subscriber Management System are trademarks of Redback Networks, Inc. All other products or services mentioned are the trademarks, service marks, registered trademarks, or registered service marks of their respective owners.

Table of Contents

About This Manual

| | |
|----------------------------|-------|
| Objectives | xxi |
| Related Publications | xxi |
| Intended Audience | xxi |
| Organization | xxi |
| Conventions | xxiii |

Chapter 1: User Interface Commands

| | |
|----------------|-----|
| ? (help) | 1-2 |
| enable | 1-4 |
| end | 1-5 |
| exit | 1-6 |

Chapter 2: Operator Exec Commands

| | |
|---------------------------|------|
| atm ping | 2-2 |
| bulkstats force | 2-4 |
| clear administrator | 2-5 |
| clear circuit | 2-6 |
| clear http | 2-8 |
| clear subscriber | 2-9 |
| clear tty | 2-10 |
| ping | 2-11 |
| show administrators | 2-13 |
| show aps | 2-15 |
| show atm counters | 2-18 |
| show atm multicast | 2-21 |
| show atm profile | 2-24 |
| show atm pvc | 2-25 |
| show atm range | 2-28 |
| show atm vp | 2-29 |
| show bindings | 2-30 |
| show bulkstats | 2-36 |
| show bypass | 2-38 |
| show clock | 2-39 |
| show context | 2-40 |
| show debugging | 2-41 |

| | |
|-----------------------------------|-------|
| show dhcp | 2-42 |
| show diag | 2-45 |
| show envmon | 2-47 |
| show frame-relay counters | 2-48 |
| show frame-relay lmi-config | 2-51 |
| show frame-relay lmi-errors | 2-53 |
| show frame-relay lmi-stats | 2-55 |
| show frame-relay multicast | 2-57 |
| show frame-relay profile | 2-60 |
| show frame-relay pvc | 2-61 |
| show hardware | 2-64 |
| show hdlc-channel counters | 2-66 |
| show hdlc-config | 2-68 |
| show ima group | 2-70 |
| show ima pmon | 2-72 |
| show ip arp | 2-75 |
| show ip bgp | 2-76 |
| show ip bgp groups | 2-78 |
| show ip bgp neighbors | 2-79 |
| show ip bgp paths | 2-82 |
| show ip bgp summary | 2-83 |
| show ip host | 2-85 |
| show ip igmp | 2-86 |
| show ip interface | 2-91 |
| show ip localhosts | 2-93 |
| show ip ospf | 2-94 |
| show ip ospf area | 2-96 |
| show ip ospf border-router | 2-98 |
| show ip ospf database | 2-99 |
| show ip ospf interface | 2-102 |
| show ip ospf neighbor | 2-104 |
| show ip pool | 2-106 |
| show ip route | 2-107 |
| show ip secured-arp | 2-110 |
| show ip socket | 2-111 |
| show ip static-route | 2-112 |
| show ip traffic | 2-114 |
| show l2f counters | 2-115 |
| show l2f info | 2-118 |
| show l2tp counters | 2-120 |
| show l2tp group | 2-126 |
| show l2tp info | 2-128 |
| show log | 2-136 |
| show logging | 2-139 |
| show memory | 2-141 |
| show ntp associations | 2-142 |
| show ntp status | 2-143 |
| show pmon | 2-145 |
| show port counters | 2-147 |
| show port diag | 2-155 |

| | |
|----------------------------|-------|
| show port info | 2-156 |
| show port table | 2-158 |
| show ppp | 2-160 |
| show pppoe | 2-163 |
| show pppoe counters | 2-164 |
| show process | 2-166 |
| show slot | 2-168 |
| show snmp server | 2-169 |
| show sram | 2-171 |
| show stack | 2-172 |
| show subscribers | 2-173 |
| show terminal | 2-175 |
| show username-format | 2-176 |
| show version | 2-177 |
| terminal length | 2-178 |
| terminal monitor | 2-179 |
| terminal width | 2-181 |
| traceroute | 2-182 |

Chapter 3: Administrator Exec Commands

| | |
|--------------------------------|------|
| aps clear | 3-2 |
| aps force | 3-3 |
| aps lockout | 3-4 |
| aps manual | 3-5 |
| bert | 3-7 |
| clear arp-cache | 3-9 |
| clear bridge table | 3-10 |
| clear counters | 3-11 |
| clear ip bgp | 3-13 |
| clear ip counter | 3-14 |
| clear ip localhosts | 3-15 |
| clear l2tp group | 3-16 |
| clear l2tp peer | 3-17 |
| clear lmi-counters | 3-18 |
| clear pmon | 3-20 |
| clear tunnel peer | 3-21 |
| clock set | 3-22 |
| configure | 3-23 |
| context | 3-25 |
| copy | 3-27 |
| debug aaa | 3-29 |
| debug all | 3-31 |
| debug aps | 3-34 |
| debug bridge span-tree | 3-35 |
| debug bridge table | 3-36 |
| debug dhcp | 3-37 |
| debug frame-relay lmi | 3-39 |
| debug frame-relay packet | 3-41 |
| debug hdlc | 3-42 |

| | |
|----------------------------------|-------|
| debug ip all | 3-43 |
| debug ip arp | 3-45 |
| debug ip bgp | 3-46 |
| debug ip ce-fe | 3-48 |
| debug ip dns | 3-49 |
| debug ip host | 3-50 |
| debug ip icmp | 3-51 |
| debug ip igmp | 3-52 |
| debug ip interface | 3-54 |
| debug ip ospf | 3-55 |
| debug ip packet | 3-56 |
| debug ip rip | 3-57 |
| debug ip route | 3-58 |
| debug ip secured-arp | 3-59 |
| debug ip telnet | 3-60 |
| debug ip tftp | 3-61 |
| debug l2tp | 3-62 |
| debug ntp | 3-64 |
| debug ppp | 3-65 |
| debug pppoe | 3-67 |
| debug radius | 3-68 |
| delete | 3-70 |
| directory | 3-71 |
| format | 3-72 |
| frame-relay-test | 3-74 |
| ip igmp join-group | 3-76 |
| ip igmp leave-group | 3-78 |
| log checkpoint | 3-80 |
| mkdir | 3-81 |
| module extract | 3-82 |
| reload | 3-84 |
| rename | 3-85 |
| rmdir | 3-86 |
| save configuration | 3-87 |
| save log | 3-89 |
| show admin-acl access-statistics | 3-91 |
| show bert | 3-92 |
| show bridge access-list | 3-93 |
| show bridge address | 3-95 |
| show bridge info | 3-96 |
| show bridge span-tree | 3-97 |
| show bridge table | 3-100 |
| show configuration | 3-101 |
| show ip access-list | 3-103 |
| show pppoe services | 3-105 |
| show service access-list | 3-106 |
| show snmp | 3-108 |
| telnet | 3-110 |

Chapter 4: Global Configuration Mode Commands

| | |
|------------------------|------|
| aaa accounting | 4-2 |
| aaa authentication | 4-4 |
| aaa default-context | 4-6 |
| aaa default-domain | 4-7 |
| aaa last-resort | 4-10 |
| aaa terse-messages | 4-12 |
| aaa update | 4-13 |
| aaa username-format | 4-15 |
| aps group | 4-17 |
| atm profile | 4-18 |
| banner motd | 4-19 |
| boot configuration | 4-20 |
| boot system | 4-22 |
| bulkstats collection | 4-24 |
| bulkstats mode | 4-25 |
| clock summer-time | 4-26 |
| clock timezone | 4-28 |
| context | 4-30 |
| dhcp preserve-state | 4-32 |
| frame-relay profile | 4-33 |
| http server | 4-34 |
| ima enable | 4-35 |
| ima group | 4-36 |
| line | 4-37 |
| logging console | 4-38 |
| logging filter | 4-40 |
| ntp mode | 4-43 |
| ntp server | 4-44 |
| port | 4-46 |
| ppp passive | 4-47 |
| pppoe services | 4-49 |
| rmon alarm | 4-50 |
| rmon event | 4-52 |
| service access-list | 4-53 |
| snmp community | 4-54 |
| snmp engine-id local | 4-56 |
| snmp group | 4-57 |
| snmp manager | 4-59 |
| snmp notify | 4-60 |
| snmp notify-filter | 4-61 |
| snmp notify-target | 4-62 |
| snmp server | 4-64 |
| snmp target | 4-66 |
| snmp target-parameters | 4-68 |
| snmp user | 4-70 |
| snmp view | 4-72 |
| system contact | 4-74 |
| system hostname | 4-75 |
| system location | 4-76 |

Chapter 5: Line Configuration Mode Commands

| | |
|--------------|-----|
| length | 5-2 |
| width | 5-3 |

Chapter 6: Bulkstats Configuration Mode Commands

| | |
|-------------------------|------|
| header format | 6-2 |
| limit | 6-4 |
| localdir | 6-6 |
| receiver | 6-8 |
| remote file | 6-10 |
| sample-interval | 6-12 |
| schema | 6-13 |
| transfer-interval | 6-15 |

Chapter 7: Context Configuration Mode Commands

| | |
|--|------|
| aaa accounting | 7-2 |
| aaa authentication administrator | 7-4 |
| aaa authentication re-try | 7-5 |
| aaa authentication subscriber | 7-7 |
| aaa authorization circuit | 7-9 |
| aaa authorization tunnel | 7-10 |
| aaa max-subscribers | 7-11 |
| aaa update | 7-13 |
| access-list undefined | 7-15 |
| administrator | 7-17 |
| as-path access-list | 7-19 |
| bridge | 7-22 |
| bridge access-list | 7-24 |
| bypass | 7-25 |
| community-list | 7-27 |
| dhcp relay option | 7-29 |
| dhcp relay server | 7-31 |
| domain | 7-32 |
| interface | 7-34 |
| ip access-group | 7-36 |
| ip access-list | 7-38 |
| ip domain-lookup | 7-40 |
| ip domain-name | 7-41 |
| ip igmp join-group | 7-42 |
| ip localhost | 7-44 |
| ip multicast-routing | 7-45 |
| ip name-servers | 7-46 |
| ip route | 7-48 |
| l2tp-peer default | 7-51 |
| l2f-peer name | 7-52 |
| l2tp-group name | 7-54 |
| l2tp-peer name | 7-56 |
| l2tp-peer unnamed | 7-58 |
| logging syslog | 7-59 |

| | |
|-----------------------------------|------|
| operator | 7-61 |
| ppp keepalive | 7-62 |
| radius accounting algorithm | 7-63 |
| radius accounting deadtime | 7-64 |
| radius accounting max-outstanding | 7-65 |
| radius accounting max-retries | 7-66 |
| radius accounting server | 7-67 |
| radius accounting timeout | 7-69 |
| radius algorithm | 7-70 |
| radius attribute filter-id | 7-71 |
| radius attribute NAS-IP-Address | 7-73 |
| radius attribute tunnel-password | 7-74 |
| radius deadtime | 7-76 |
| radius max-outstanding | 7-77 |
| radius max-retries | 7-78 |
| radius server | 7-80 |
| radius strip-domain | 7-82 |
| radius timeout | 7-84 |
| route-access-list | 7-85 |
| route-map | 7-87 |
| router bgp | 7-89 |
| router-id | 7-90 |
| router igmp-proxy | 7-91 |
| router ospf | 7-92 |
| router rip | 7-93 |
| subscriber | 7-94 |

Chapter 8: Administrator Configuration Mode Commands

| | |
|---------|-----|
| timeout | 8-2 |
|---------|-----|

Chapter 9: Interface Configuration Mode Commands

| | |
|------------------------|------|
| bridge-group | 9-2 |
| description | 9-4 |
| dhcp relay size | 9-5 |
| ip access-group | 9-7 |
| ip address | 9-9 |
| ip arp arpa | 9-11 |
| ip arp timeout | 9-12 |
| ip igmp | 9-13 |
| ip igmp mode | 9-15 |
| ip interface-cost | 9-16 |
| ip lookup host | 9-17 |
| ip mask-reply | 9-18 |
| ip mtu | 9-19 |
| ip pool | 9-20 |
| ip rip listen | 9-21 |
| ip rip receive version | 9-22 |
| ip rip send version | 9-23 |
| ip rip split-horizon | 9-24 |

| | |
|----------------------|------|
| ip rip supply | 9-25 |
| ip secured-arp | 9-26 |

Chapter 10: Subscriber Configuration Mode Commands

| | |
|-------------------------------|-------|
| bridge-group | 10-2 |
| dhcp max-addrs | 10-4 |
| dns | 10-5 |
| ip access-group | 10-6 |
| ip address | 10-7 |
| ip arp | 10-9 |
| ip multicast max-groups | 10-10 |
| ip multicast receive | 10-11 |
| ip multicast send | 10-13 |
| ip route | 10-15 |
| ip source-validation | 10-16 |
| ip tos-field | 10-17 |
| l2tp-tunnel domain | 10-18 |
| l2tp-tunnel name | 10-19 |
| outbound password | 10-20 |
| password | 10-21 |
| police | 10-22 |
| ppp mtu | 10-23 |
| pppoe motm | 10-24 |
| pppoe url | 10-25 |
| rate-limit | 10-27 |
| timeout | 10-28 |
| tunnel domain | 10-29 |
| tunnel name | 10-31 |

Chapter 11: ATM Profile Configuration Mode Commands

| | |
|------------------------------------|-------|
| buffers | 11-2 |
| bulkstats schema | 11-3 |
| clpbit | 11-5 |
| counters | 11-6 |
| radius attribute medium-type | 11-8 |
| serviceclass | 11-10 |
| shaping | 11-12 |

Chapter 12: APS Configuration Mode Commands

| | |
|----------------------|------|
| ports | 12-2 |
| signal-degrade | 12-4 |

Chapter 13: IMA Group Configuration Mode Commands

| | |
|-----------------------|------|
| clock mode | 13-2 |
| clock source | 13-3 |
| delay-tolerance | 13-4 |
| description | 13-5 |
| frame-length | 13-6 |

| | |
|---------------------|------|
| minimum-links | 13-7 |
| ports | 13-8 |
| symmetry | 13-9 |

Chapter 14: Frame Relay Profile Configuration Mode Commands

| | |
|------------------------------------|------|
| buffers transmit | 14-2 |
| bulkstats schema | 14-3 |
| counters | 14-5 |
| radius attribute medium-type | 14-7 |

Chapter 15: Port Configuration Mode Commands

| | |
|------------------------------------|-------|
| bulkstats schema | 15-3 |
| description | 15-5 |
| police | 15-6 |
| rate-limit | 15-7 |
| shutdown | 15-8 |
| 8khztiming (DS-3 only) | 15-10 |
| atm pvc | 15-11 |
| atm pvc default | 15-15 |
| atm vp | 15-17 |
| buffers | 15-19 |
| cell-delineation (DS-3 only) | 15-20 |
| circuit creation | 15-21 |
| circuit prefix-string | 15-23 |
| circuit range | 15-25 |
| clock-source | 15-27 |
| framing stm1 (OC-3 only) | 15-28 |
| idle-cell | 15-29 |
| length (DS-3 only) | 15-30 |
| loopback | 15-31 |
| scramble | 15-32 |
| atm pvc | 15-34 |
| atm pvc default | 15-37 |
| buffers | 15-39 |
| cablelength | 15-40 |
| clock-source | 15-41 |
| circuit creation | 15-42 |
| circuit prefix-string | 15-44 |
| circuit range | 15-46 |
| fdl | 15-48 |
| framing | 15-49 |
| linecode | 15-50 |
| loopback | 15-51 |
| scramble | 15-52 |
| yellow-alarm | 15-53 |
| bind authentication | 15-55 |
| bind bypass | 15-57 |
| bind interface | 15-59 |
| bind l2tp-session | 15-61 |

| | |
|--------------------------------------|--------|
| bind multi | 15-62 |
| bind session | 15-64 |
| buffers | 15-66 |
| encapsulation | 15-67 |
| ip host | 15-68 |
| loopback | 15-69 |
| medium | 15-70 |
| radius attribute medium-type | 15-71 |
| bind authentication | 15-73 |
| bind bypass | 15-75 |
| bind interface | 15-77 |
| bind l2tp-session | 15-79 |
| bind session | 15-80 |
| bind subscriber | 15-82 |
| buffers | 15-84 |
| circuit creation | 15-85 |
| circuit prefix-string | 15-87 |
| clock-source (DS-3 only) | 15-89 |
| encapsulation | 15-90 |
| frame-relay auto-detect | 15-91 |
| frame-relay intf-type | 15-93 |
| frame-relay keepalive | 15-95 |
| frame-relay lmi-n391dte | 15-96 |
| frame-relay lmi-n392dce | 15-97 |
| frame-relay lmi-n392dte | 15-98 |
| frame-relay lmi-n393dce | 15-99 |
| frame-relay lmi-n393dte | 15-100 |
| frame-relay lmi-t392dce | 15-101 |
| frame-relay lmi-type | 15-102 |
| frame-relay pvc | 15-103 |
| frame-relay pvc default | 15-106 |
| framing (DS-3 only) | 15-108 |
| hardware-interface (HSSI only) | 15-109 |
| keepalive | 15-110 |
| length (DS-3 only) | 15-111 |
| loopback | 15-112 |
| bind authentication | 15-115 |
| bind bypass | 15-117 |
| bind interface | 15-119 |
| bind l2tp-session | 15-121 |
| bind session | 15-122 |
| bind subscriber | 15-123 |
| buffers | 15-125 |
| cablelength (packet T1 only) | 15-126 |
| clock-source | 15-127 |
| encapsulation | 15-128 |
| fdl (packet T1 only) | 15-129 |
| framing | 15-130 |
| invert-data | 15-131 |
| keepalive | 15-132 |

| | |
|---------------------------------|--------|
| linecode (packet T1 only) | 15-133 |
| loopback | 15-134 |
| speed | 15-135 |
| timeslot | 15-136 |
| ts16 | 15-137 |
| yellow-alarm | 15-138 |
| buffers | 15-140 |
| clock-source | 15-141 |
| framing | 15-142 |
| hdlc-channel | 15-143 |
| length | 15-144 |
| loopback | 15-145 |
| t1 | 15-146 |

Chapter 16: Circuit Configuration Mode Commands

| | |
|----------------------------|-------|
| bind authentication | 16-2 |
| bind auto-subscriber | 16-4 |
| bind bypass | 16-6 |
| bind dot1q | 16-8 |
| bind interface | 16-10 |
| bind l2tp-session | 16-12 |
| bind multi | 16-13 |
| bind session | 16-15 |
| bind subscriber | 16-17 |
| bind l2tp-tunnel | 16-19 |
| description | 16-20 |
| ip host | 16-21 |
| mac address | 16-23 |

Chapter 17: HDLC Channel Configuration Mode Commands

| | |
|-----------------------------|-------|
| bind authentication | 17-3 |
| bind bypass | 17-5 |
| bind interface | 17-7 |
| bind l2tp-session | 17-9 |
| bind session | 17-10 |
| bind subscriber | 17-12 |
| bulkstats schema | 17-14 |
| circuit creation | 17-17 |
| circuit prefix-string | 17-19 |
| crc | 17-21 |
| encapsulation | 17-22 |
| invert-data | 17-24 |
| keepalive | 17-25 |
| loopback | 17-26 |
| shutdown | 17-27 |
| speed | 17-28 |

Chapter 18: T1 Channel Configuration Mode Commands

| | |
|--------------------|------|
| clock-source | 18-2 |
| fdl | 18-3 |
| framing | 18-4 |
| loopback | 18-5 |
| yellow-alarm | 18-6 |

Chapter 19: Route Map Configuration Mode Commands

| | |
|----------------------------|-------|
| match as-path | 19-2 |
| match community-list | 19-3 |
| match interface | 19-4 |
| match ip address | 19-5 |
| match ip next-hop | 19-6 |
| match metric | 19-7 |
| match route-type | 19-8 |
| match tag | 19-9 |
| set as-path | 19-10 |
| set community | 19-12 |
| set ip next-hop | 19-14 |
| set local-preference | 19-16 |
| set metric | 19-17 |
| set origin | 19-18 |
| set preference | 19-19 |

Chapter 20: RIP Configuration Mode Commands

| | |
|--------------------|------|
| auto-summary | 20-2 |
| network | 20-3 |
| precedence | 20-5 |
| redistribute | 20-7 |
| version | 20-9 |

Chapter 21: BGP Configuration Mode Commands

| | |
|--------------------------|------|
| aggregate-address | 21-2 |
| always-compare-med | 21-4 |
| export-non-active | 21-5 |
| group | 21-6 |
| precedence | 21-7 |
| redistribute | 21-9 |

Chapter 22: BGP Group Configuration Mode Commands

| | |
|---------------------------|-------|
| accept-med | 22-2 |
| default-originate | 22-3 |
| hold-time | 22-4 |
| maximum-prefix | 22-5 |
| maximum-prefix-warn | 22-6 |
| metric-out | 22-7 |
| neighbor | 22-8 |
| nexthop-self | 22-9 |
| no-aggregator-id | 22-10 |

| | |
|-------------------|-------|
| out-delay | 22-11 |
| passive | 22-12 |
| precedence | 22-13 |
| preference | 22-15 |
| remove-private-AS | 22-16 |
| throttle | 22-17 |
| ttl | 22-18 |

| | |
|---|-------|
| Chapter 23: BGP Peer Configuration Mode Commands | |
| accept-med | 23-2 |
| allow-bad-routerid | 23-3 |
| enable-peer | 23-4 |
| hold-time | 23-5 |
| maximum-prefix | 23-6 |
| maximum-prefix-warn | 23-7 |
| metric-out | 23-8 |
| nexthop-self | 23-9 |
| no-aggregator-id | 23-10 |
| out-delay | 23-11 |
| passive | 23-12 |
| precedence | 23-13 |
| preference | 23-15 |
| remove-private-AS | 23-16 |
| route-map | 23-17 |
| ttl | 23-18 |

| | |
|---|------|
| Chapter 24: OSPF Configuration Mode Commands | |
| area | 24-2 |
| precedence | 24-3 |
| redistribute | 24-5 |
| spf-timers | 24-6 |

| | |
|--|------|
| Chapter 25: OSPF Area Configuration Mode Commands | |
| areatype | 25-2 |
| ospf-interface | 25-3 |

| | |
|---|------|
| Chapter 26: OSPF Interface Configuration Mode Commands | |
| authentication | 26-2 |
| cost | 26-3 |
| hello-interval | 26-4 |
| retransmit-interval | 26-5 |
| routerdead-interval | 26-6 |
| transmit-delay | 26-7 |

| | |
|--|------|
| Chapter 27: IGMP Proxy Router Configuration Mode Commands | |
| router-igmp-interface | 27-2 |

Chapter 28: IGMP Configuration Mode Commands

| | |
|-----------------------------------|-------|
| def-version | 28-2 |
| last-member-query-interval | 28-3 |
| query-interval | 28-5 |
| query-response-interval | 28-7 |
| robustness | 28-9 |
| startup-query-interval | 28-11 |
| unsolicited-report-interval | 28-13 |
| version1-router-interval | 28-15 |

Chapter 29: Bridge Configuration Mode Commands

| | |
|--------------------|------|
| bridge-only | 29-2 |
| forward-time | 29-3 |
| hello-time | 29-4 |
| max-age | 29-5 |
| priority | 29-6 |
| protocol | 29-7 |

Chapter 30: L2TP Configuration Mode Commands

| | |
|------------------------------|-------|
| description | 30-2 |
| dnis | 30-4 |
| domain | 30-5 |
| ethernet encapsulation | 30-7 |
| ethernet session | 30-8 |
| flow-control | 30-10 |
| function | 30-11 |
| local-name | 30-13 |
| max-sessions | 30-14 |
| max-tunnels | 30-15 |
| police | 30-16 |
| rate-limit | 30-17 |
| retry | 30-19 |
| session-auth | 30-20 |
| static | 30-22 |
| timeout | 30-23 |
| tunnel-auth | 30-24 |
| tunnel-window | 30-25 |

Chapter 31: L2TP Group Configuration Mode Commands

| | |
|-------------------|-------|
| algorithm | 31-2 |
| deadtime | 31-6 |
| description | 31-8 |
| domain | 31-10 |
| peer-name | 31-11 |

Chapter 32: L2F Configuration Mode Commands

| | |
|-------------------|------|
| description | 32-2 |
| domain | 32-4 |

| | |
|--------------------|-------|
| function | 32-6 |
| local-name | 32-7 |
| max-sessions | 32-8 |
| max-tunnels | 32-9 |
| police | 32-10 |
| rate-limit | 32-11 |
| retry | 32-13 |
| session-auth | 32-14 |
| timeout | 32-16 |
| tunnel-auth | 32-17 |

Chapter 33: Bypass Configuration Mode Commands

| | |
|-------------------|------|
| description | 33-2 |
|-------------------|------|

Chapter 34: NTP Configuration Mode Commands

| | |
|----------------|------|
| slowsync | 34-2 |
|----------------|------|

Chapter 35: Access Control List Configuration Mode Commands

| | |
|---|-------|
| {permit deny} | 35-4 |
| {permit deny} lsap | 35-6 |
| {permit deny} type | 35-8 |
| {permit deny} | 35-11 |
| {permit deny} icmp | 35-13 |
| {permit deny} igmp | 35-15 |
| {permit deny} ip | 35-18 |
| {permit deny} {tcp udp} | 35-20 |
| redirect interface next-hop | 35-23 |
| redirect interface next-hop icmp | 35-25 |
| redirect interface next-hop ip | 35-27 |
| redirect interface next-hop {tcp udp} | 35-29 |

Chapter 36: Service Access List Configuration Mode Commands

| | |
|-------------------------------|------|
| {permit deny} any | 36-3 |
| {permit deny} context | 36-5 |
| {permit deny} domain | 36-7 |

Index

ethernet encapsulation

ethernet encapsulation ppp over-ethernet

default ethernet encapsulation

Purpose

Specifies the type of Ethernet encapsulation to be used for any Ethernet on the L2TP peer.

Syntax Description

ppp over-ethernet

Specifies that the type of Ethernet encapsulation to be used is PPP over Ethernet (PPPoE).

Default

IP/bridging encapsulation is selected for Ethernet over L2TP sessions if this command is not used.

Usage Guidelines

At this time, PPPoE is the only encapsulation option available using this command. If this command is not issued, the encapsulation for the peer is set to IP/bridging for Ethernet over L2TP sessions.

Use this command when you want to be able to have Ethernet encapsulated sessions through L2TP tunnels.

The default form of this command resets the encapsulation to IP/bridging.

Examples

The following example sets the Ethernet encapsulation on an L2TP peer to PPPoE:

```
[local] RedBack (config-ctx) #l2tp-peer name peer1
[local] RedBack (config-l2tp) #ethernet encapsulation ppp over-ethernet
```

Related Commands

l2tp-peer name
l2tp-peer unnamed
show l2tp info

ethernet session

ethernet session {{**auth** {**pap** | **chap** | **chap pap**} [**maximum sessions**] [**context name** | **service-group name**]} | **interface** *interface context*}

no ethernet session

Purpose

Specifies the authentication method to be used for the Ethernet session on the L2TP peer.

Syntax Description

| | |
|------------------------------------|---|
| auth pap | Specifies that Password Authentication Protocol (PAP) be used to obtain the username and password from the subscriber. |
| auth chap | Specifies that Challenge Handshake Authentication Protocol (CHAP) be used to obtain the username and password from the subscriber. |
| auth chap pap | Specifies that either PAP or CHAP can be used to obtain the username and password from the subscriber, but that CHAP is preferred. |
| maximum sessions | Optional when auth is specified. Maximum number of PPPoE sessions allowed per L2TP session. Valid range is 0 (which means there is no maximum) through 8000. The default value is 0. |
| context name | Optional when auth is specified. Restricts PPPoE sessions with Ethernet encapsulation on the circuits and ports being bound to the specified context. |
| service-group name | Optional when auth is specified. Limits the services available to the circuit or port to those permitted by the named service access list. |
| interface interface context | The name of the interface to which the Ethernet session is to be bound and the name of the context within which the interface exists. |

Default

None

Usage Guidelines

The **auth** and **interface** constructs are mutually exclusive. The **auth** construct is only available when the session is PPPoE with Ethernet encapsulation. Otherwise, the **interface** construct is available. The authentication controlled by the **auth** construct is only for the Ethernet-encapsulated PPPoE session carried by the tunnel, not any PPP sessions that might also be present. For the PPP sessions, the **session auth** command controls the authentication method.

The **no** form of this command removes the setting.

Examples

The following example shows setting the authentication method for an Ethernet-encapsulated PPPoE session:

```
[local] RedBack(config-ctx)#l2tp-peer name peer1
[local] RedBack(config-l2tp)#ethernet session auth chap pap
```

Related Commands

l2tp-peer name
l2tp-peer unnamed
show l2tp info

Ex. C

Release Notes for Redback AOS Release 3.1.4

**April 2000
Part Number 220-0121-03**



Corporate Headquarters
Redback Networks, Inc.
1389 Moffett Park Drive
Sunnyvale, CA 94089-1134
USA
<http://www.redback.com>
Tel: 408 548-3500

Contents

Hardware Compatibility, page 5

Supported Interfaces, page 5

- SMS 1000 and SMS 1800, page 5
- SMS 500, page 5

What's New in Release 3.1.3, page 6

- Routing, page 6
- IP Software, page 6
- L2F, page 7
- L2TP, page 7
- ATM, page 7
- Service Access Lists, page 7
- AAA, page 7
- Network Management, page 8
- Miscellaneous Enhancements, page 8

What's New in Release 3.1.4, page 9

- Bulkstats, page 9
- IP Software, page 10
- Network Management, page 10
- Miscellaneous Enhancements, page 10

Upgrading to Redback AOS Release 3.1, page 10

- Booting via the Local Flash File System, page 11
- Booting via TFTP from an Explicit Image, page 11
- Booting via TFTP from an Image Specified by a BOOTP Server, page 13

Enhancements and Resolved Issues (3.1.4), page 13

- Routing, page 13
- IP Software, page 14
- L2TP/L2F, page 14

-
- AAA, page 15
 - Network Management, page 15
 - Bulkstats, page 9
 - Miscellaneous, page 16

Documentation Errata, page 17

- SMS 1000/1800 Hardware Guide, page 17
- AOS Configuration Guide, page 17
- AOS Command Reference, page 19

Caveats and Known Problems, page 30

- FE2 Upgrade, page 30
- Hot-Swap Capabilities, page 30
- IP Routing, page 30
- IP Source-Address Validation, page 30
- ATM T1 IMA, page 30
- Web Management, page 31
- Miscellaneous, page 31

Contacting Customer Support, page 31

L2F

AOS Release 3.1 includes support for Cisco's Layer 2 Forwarding (L2F) protocol. You can configure the SMS to operate as a Network Access Server (NAS) or Home Gateway (HG) for UDP/IP-based tunnels.

L2TP

AOS Release 3.1 includes the following L2TP enhancements:

- Fixed service selection—You can configure an LNS to hardwire PPP sessions that arrive from an L2TP peer to a specific context. This feature enables you to disable dynamic service selection for the PPP sessions that arrive from an L2TP peer.
- Ethernet over tunnels—You can now tunnel Ethernet (including bridged 1483 and bridged 1490 circuits) over an L2TP tunnel. A tunnel can support both Ethernet and PPPoE traffic concurrently.
- Per-session ID string over tunnels—When running as an LNS, AOS now adds the originating LAC's local name as the session ID string.
- Additional L2TP counters—The **show l2tp counters** and **show l2tp info** operator exec commands now include established sessions, total established sessions, and total failed sessions counters in the command output.
- L2TP AVPs—AOS Release 3.1 includes several new vendor-specific L2TP attribute-value pairs (AVPs). See Appendix F, "L2TP Attribute Value Pairs," in the *Access Operating System (AOS) Configuration Guide*.

ATM

- ATM IMA—AOS Release 3.1 supports the ATM Forum Inverse Multiplexing for ATM (IMA) Version 1.0 (AF-PHY-0086.000) and Version 1.1 (AF-PHY-0086.001) specifications. Using the IMA feature, you can configure multiple ports on an ATM T1 I/O module to operate as a single link.
- Increased VCI range—The range of VCIs for ATM Version 2 I/O modules is 1 through 65535 for ATM Version 2 I/O modules.
- GFR traffic shaping—Use the new **gfr** option for the **shaping** ATM profile configuration command to specify shaping based on Guaranteed Frame Rate. GFR is supported on ATM Version 2 I/O modules only.
- Shaped virtual paths—Use the new **atm vp** port configuration command to create a shaped virtual path. Virtual paths are supported on ATM Version 2 I/O modules only.

Service Access Lists

You can define service access lists to restrict the available services (such as contexts and tunnels) available to subscribers on a per-circuit basis.

AAA

AOS Release 3.1 supports the following new AAA features and enhancements: